

Estimate for :- supply &amp; erection of bracket &amp; led fittings at Y shap bridge m.c-Dwrf (C.C)

S No	DESCRIPTION As per SOR CGPWD Elect. Rules DT 01/07/15	unit	Rate
(1) $\frac{145}{21-22}$ 3	Painting of following height-steel Tubular poles with two coat of approved colour and shade Synthetic enamel Paint including cleaning the surface as required  Above 8 mtr and up to 10 mtr	Each	
(2)	supply and fixing following street light pole bracket on existing pole made out of 50 mm dia M.S. "B" class pipe welded to 300 mm long M.S pole canopy of suitable dia at a angle of 102.50 including having MS triangular stiffener of size 150x50x5 mm thick making arrangement for lighting the bracket with pole by providing suitable size heavy duty nuts and bolts in canopy painting with one coat of approved steel primer etc. as req.  141/21.9.2 :- Single overhang 1.00 mtr Long 141/21.9.5 :- Double overhang 1.0 mtr Long	Each Each	
(3)	supplying and fixing pvc watertight terminal box of approved make and brand with detachable gland plate in bottom hinged front oprable cover rubber gasket- having 1 nos 4 way connector and 1 no. SP MCB inside the box for cable connection fixed to pole with 2 nos clamp made from 25x3 mm GI plate with 2 no. GI nuts bolts complete as required.  143/21-17-2 :- 300x200x125 mm for 3 phase	Each	
(4)	Providing and fixing following size FR PVC insulated PVC sheathed flexible copper conductor cable on the floor/wall or side of the table/door etc as required.  1.0 sq mm three core	mtr.	

office of The municipal corporation, Durg CC

estimate for

SNo	DESCRIPTION	Unit	Rate
15)	Supplying Installation testing and commissioning of following 230/250 volts LED street light fittings with all accessories like driver heat sink made of die cast aluminium with IP 66 Protection and 5KV surge protector on pole bracket complete as required and furnishing 2 yrs Guarantee Certificate from manufacturer.	each	
	45/8.30.4 90 watt		

Ans